

CONFIDENTIAL

Copy 6

SECURITY INFORMATION

RM A52J31

NACA RM A52J31

JAN 14 1953



RESEARCH MEMORANDUM

WIND-TUNNEL INVESTIGATION AT SUBSONIC AND SUPERSONIC SPEEDS OF A
MODEL OF A TAILLESS FIGHTER AIRPLANE EMPLOYING A LOW-ASPECT-
RATIO SWEEPED-BACK WING - EFFECTS OF EXTERNAL FUEL TANKS
AND ROCKET PACKETS ON THE DRAG CHARACTERISTICS

By Willard G. Smith

Ames Aeronautical Laboratory
Moffett Field, Calif.

CLASSIFICATION CHANGED
UNCLASSIFIED

To _____

By authority of Assoc. + P.A. 9 ^{Effective} Date 9-1-59

HB 11-23-57

CLASSIFIED DOCUMENT

This material contains information affecting the National Defense of the United States within the meaning of the espionage laws, Title 18, U.S.C., Sec. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WASHINGTON

January 12, 1953

CONFIDENTIAL
UNCLASSIFIED

NACA LIBRARY
LANGLEY AERONAUTICAL LABORATORY
Langley Field, Va.

UNCLASSIFIED

NACA RM A52J31



3 1176 01434 8156

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

WIND-TUNNEL INVESTIGATION AT SUBSONIC AND SUPERSONIC SPEEDS OF A
MODEL OF A TAILLESS FIGHTER AIRPLANE EMPLOYING A LOW-ASPECT-
RATIO SWEEPED-BACK WING - EFFECTS OF EXTERNAL FUEL TANKS
AND ROCKET PACKETS ON THE DRAG CHARACTERISTICS

By Willard G. Smith

SUMMARY

The effects of external fuel tanks and externally mounted rocket packets on the drag characteristics of a model of a tailless fighter airplane are presented in this report. The investigation was conducted through a Mach number range of 0.60 to 0.90 and 1.20 to 1.70 at a constant Reynolds number of 3.2 million. The measured lift, drag, pitching-moment, and rolling-moment coefficients and lift-drag ratios are presented in tabular form and the drag characteristics and lift-drag ratios are also presented in graphic form. In addition, pressure distribution data are tabulated which may be used to determine the influence of the external stores on the wing load distribution at supersonic speeds.

Results of this investigation show that the addition of two external fuel tanks and four faired rocket packets to the model produced drag increments which increased from 30 percent to 50 percent of the drag of the basic model between Mach numbers of 0.60 and 0.90, respectively, while at supersonic Mach numbers this drag increment was approximately 30 percent of the drag of the basic model. Tests of the model fitted with four rocket packets indicate that the drag may be reduced at subsonic speeds by fairing the open rocket packets, but at supersonic speeds the faired packets produced more drag. A small decrease in drag was realized at supersonic speeds, for the model fitted with two fuel tanks and four rocket packets, by mounting the outboard packets and fuel tanks in a more forward chordwise position with respect to the wing.

INTRODUCTION

Knowledge of the increases in drag to be expected from the addition of externally mounted fuel tanks and armament under the wings and fuselage becomes increasingly important as the trend continues toward long-range, high-speed fighter airplanes carrying rocket-propelled armament. An

~~CONFIDENTIAL~~

UNCLASSIFIED

investigation of the effects of this type of external installation on the aerodynamic characteristics of a model having a low-aspect-ratio swept-back wing has been conducted in the Ames 6- by 6-foot supersonic wind tunnel. The model was fitted with various combinations of under-the-wing type rocket-packet and fuel-tank installations and tested at subsonic and supersonic Mach numbers at a constant Reynolds number. Two chordwise locations of the fuel tanks and rocket packets were investigated and the rocket packets were tested with the ends of the packets faired smooth and with the rocket tubes open. The results of this investigation are presented herein. The results of an investigation of the stability and control characteristics of this same model conducted in the Ames 6- by 6-foot supersonic wind tunnel are presented in reference 1.

NOTATION

The lift, drag, and pitching-moment coefficients are referred to the stability axes with the origin at the quarter-chord point of the mean aerodynamic chord projected to the fuselage center line. Rolling-moment coefficients are referred to the fuselage longitudinal axis.

b	wing span, feet
c	local wing chord measured parallel to plane of symmetry, feet
\bar{c}	wing mean aerodynamic chord $\left(\frac{\int_0^{b/2} c^2 dy}{\int_0^{b/2} c dy} \right)$, feet
C_D	drag coefficient $\left(\frac{\text{drag}}{qS} \right)$
C_{D_B}	increment of drag coefficient due to external-store installation or fuselage modification based on total wing area ($C_{D_{\text{model}}} + \text{store} - C_{D_{\text{model}}}$)
C_L	lift coefficient $\left(\frac{\text{lift}}{qS} \right)$
C_l	rolling-moment coefficient $\left(\frac{\text{rolling moment}}{qSb} \right)$
C_m	pitching-moment coefficient $\left(\frac{\text{pitching moment}}{qS\bar{c}} \right)$
C_p	static pressure coefficient $\left(\frac{p-p_o}{q} \right)$
$\frac{L}{D}$	lift-drag ratio

$\left(\frac{L}{D}\right)_{\max}$	maximum lift-drag ratio
M	free-stream Mach number
p	local static pressure, pounds per square foot
p _o	free-stream static pressure, pounds per square foot
q	free-stream dynamic pressure, pounds per square foot
R	Reynolds number, based on the mean aerodynamic chord
S	total projected wing area, including area formed by extending leading and trailing edges to plane of symmetry, square feet
Y	spanwise distance from plane of symmetry, feet
α	angle of attack of fuselage longitudinal axis, degrees

APPARATUS

Wind Tunnel and Equipment

The present investigation was conducted in the Ames 6- by 6-foot supersonic wind tunnel. This is a closed-return, variable-pressure wind tunnel in which the pressure and Mach number can be continuously varied. The stagnation pressure can be varied from 2 to 17 pounds per square inch absolute and the Mach number can be varied from 0.60 to 0.90 and from 1.15 to 2.00. A complete description of the wind tunnel is given in reference 2.

The model was sting mounted with the pitch plane of the model horizontal in the wind tunnel to utilize the most uniform stream conditions. (See reference 2). A four-component electrical strain-gage balance, similar in design to that used in reference 3, was enclosed within the fuselage of the model. The aerodynamic forces and moments were registered by recording-type galvanometers calibrated by applying known loads to the balance.

Model

A model of a high-speed fighter airplane having a low-aspect-ratio, swept-back wing and a swept-back vertical tail but not horizontal tail was used in this investigation (fig. 1). A bubble-type canopy was faired into a dorsal fin which extended back to the vertical tail. Provisions

were made for fairing the vertical tail into the fuselage when the canopy and dorsal fin were removed. The wing had a leading-edge sweep angle of 52.5° and a taper ratio of 0.332 based on the theoretical wing tip. The wing was composed of symmetrical sections in streamwise planes having a thickness of 7.0 percent of the chord at the wing root tapering to 4.5 percent of the chord at the theoretical wing tip.

The model was fitted with inlets housed in wing-body juncture fairings with internal ducts allowing the air to flow through and exhaust at the rear of the fuselage. In this investigation the mass flow of air through the ducts was not adjustable; however, the ducts were constructed so that at supersonic speeds the exit was choked, limiting the inlet Mach number to 0.4. In order to accommodate the annular duct exit and the mounting sting, the boattailing on the model was somewhat less than would be expected on a full-scale airplane.

Rocket packets and fuel tanks were provided, to be attached to the wings in the locations shown in figures 2 and 3. The outboard rocket packets and the fuel tanks were mounted on unswept and swept-forward pylons as shown in figures 2 and 3. The purpose of the swept-forward pylons was to obtain a more forward location of these stores. The rocket packets were tested both with the fore and aft ends of the rocket packet faired smooth and with six holes open through the packet, to simulate conditions before and after firing the rockets.

Provisions were made to measure pressure distribution data at five spanwise stations as shown in figure 4. The location of the orifices on the upper and lower surfaces of the port wing are given in table I.

TESTS AND PROCEDURE

As a basis for comparison, tests were made of the basic model with canopy and dorsal fin in place and with no external stores installed. Lift, drag, pitching-moment, and rolling-moment data were obtained at Mach numbers of 0.60, 0.80, 0.90, 1.20, 1.35, 1.50, and 1.70 at a constant Reynolds number of 3.2 million, through an angle of attack range of -2° to $+8^\circ$. Similar data were then obtained at corresponding test conditions for the following model configurations:

1. Basic model fitted with inboard and outboard faired rocket packets mounted on unswept pylons
2. Basic model fitted with inboard and outboard open-tube rocket packets mounted on unswept pylons
3. Basic model fitted with two external fuel tanks mounted on unswept pylons

4. Basic model fitted with inboard and outboard faired rocket packets and two external fuel tanks all mounted on unswept pylons
5. Basic model fitted with outboard faired rocket packets and two external fuel tanks mounted on swept pylons and inboard faired rocket packets mounted on unswept pylons
6. Basic model with canopy and dorsal fin removed (no external stores)

Pressure distribution data were obtained for the basic model and for the model fitted with four faired rocket packets mounted on straight pylons. These tests were conducted at Mach numbers of 1.20, 1.30, and 1.70 at a Reynolds number of 2.0 million. Data were obtained through an angle-of-attack range of -3° to $+12^\circ$ at 2° increments for the basic model and 4° increments for tests of the model fitted with the rocket packets. A tabulation of the test conditions is presented in table II.

Reduction of Data

The test data have been reduced to standard NACA coefficient form based on the total projected wing area including the area in the region formed by extending the leading and trailing edges to the plane of symmetry (fig. 1). Factors which could affect the accuracy of these results and the corrections applied are discussed in the following paragraphs.

Angle of attack.- The determination of the actual angle of attack of the model under load required several corrections to be applied to the nominal angle. Corrections, determined from static load calibrations, were applied for the angular deflection of the sting and balance under aerodynamic load and for the angular movement due to structural clearance in the model support and balance. These corrections amounted to from 5 to 10 percent of the nominal angle, depending on the load.

Tunnel-wall interference.- Corrections to the data for the effects of the tunnel walls at subsonic speeds were made by the method of reference 4. These corrections which were added to the data were as follows:

$$\Delta\alpha = 0.377 C_L$$

$$\Delta C_D = 0.0066 C_L^2$$

The reflected bow wave did not intersect the model and so no tunnel-wall corrections were made for supersonic Mach numbers.

The effect of constriction of the flow at subsonic speeds due to the presence of the model was taken into account by the method of reference 5. This correction was calculated for conditions of zero angle of attack and was applied through the angle-of-attack range. At a Mach number of 0.90, this correction amounted to a 1-percent increase in Mach number and dynamic pressure over those values determined from calibrations of the wind tunnel without a model in place.

Support interference.- Results of a wind-tunnel test of a similar model (reference 6) show that the effects of support interference consisted primarily of a change of pressure at the base of the model. In this test the base pressure was measured and corrections were applied to adjust the pressure at the base to free-stream static pressure.¹ The drag values are, therefore, forebody drag coefficients.

Stream variations.- Tests were made at subsonic and supersonic speeds with the model in upright and inverted attitudes. Results of these tests showed no measurable indications of stream angle or stream curvature in the horizontal plane of the wind tunnel. Stream surveys of the Ames 6- by 6-foot supersonic wind tunnel (reference 2) show some curvature in the vertical plane of the wind tunnel, but the results of a subsequent investigation (reference 7) indicate that this curvature has little effect on the longitudinal aerodynamic characteristics of the model when pitched in the horizontal plane.

Internal duct drag.- The model was equipped with twin ducts through which air could flow. However, provisions were not made to vary the mass flow, so a study of the duct drag characteristics was not feasible in this investigation. The drag data presented herein are for the complete model; that is, the drag due to flow through the ducts has not been subtracted from the final drag coefficients.

Precision of Data

The accuracy of the test results, excluding stream effects, is shown by the repeatability of the data. Examination of the results showed the data to repeat with the accuracy shown in the following table:

¹The base area used in this investigation was the entire base area of the model less the duct exit area.

Quantity	Accuracy	
	$C_L = 0$	$C_L = 0.25$
C_D	± 0.0004	± 0.0006
C_L	± 0.0016	± 0.0018
C_m	± 0.0005	± 0.0005
C_l	± 0.0006	± 0.0009
C_p	± 0.005	± 0.005
M	± 0.03	± 0.03
R	$\pm 0.03 \times 10^6$	$\pm 0.03 \times 10^6$
α	± 1	± 15

The precision of the data presented herein is superior to that of the data in reference 1 because these data were obtained for a consecutive series of tests in the wind tunnel and the mounting of the model and balance was unchanged during this investigation.

RESULTS AND DISCUSSION

Only the data pertinent to a study of the effects of external fuel tanks and rocket packets on the drag characteristics of the model are discussed in this report. All the force and moment data obtained from these tests, including lift and rolling-moment coefficients and lift-drag ratios, are presented in table III, however. In addition, experimental static pressure coefficients obtained at Mach numbers of 1.20, 1.30, and 1.70 for the basic model and for the model fitted with four rocket packets are presented in table IV. Comparison of the data from these pressure distribution tests gives an indication of the effects of the rocket-packet installation on the air loads experienced by the model.

The effects of external stores on the drag characteristics of the model are presented in this report as the increments of drag coefficient incurred by the addition of external stores. Figure 5 presents the variation of drag coefficient with lift coefficient for the basic model at Mach numbers of 0.60, 0.80, 0.90, 1.20, 1.35, 1.50, and 1.70. As previously mentioned, the drag coefficients presented in this report include the internal duct drag. The increments of drag coefficient for the various store installations investigated are shown in figure 6 as a function of Mach number for 0 and 0.25 lift coefficients. This figure shows that at subsonic speeds the drag increment resulting from the addition of four rocket packets was somewhat less when the packets were faired, but at supersonic speeds fairing the packets increased the drag. The drag increments for two fuel tanks and four rocket packets, mounted in the aft chordwise location (unswept pylons), varied from approximately 30 percent of the drag of the basic model at a Mach number of 0.60 to 50 percent at

a Mach number of 0.90. For Mach numbers of 1.20 to 1.70 the drag increment for these same external-store configurations was approximately 30 percent of the drag of the basic model. Results of tests of the model with the stores mounted in two chordwise locations showed that the change in chordwise location had no significant effect on the drag at subsonic speeds. At supersonic speeds, however, the drag increment resulting from the addition of two fuel tanks and four rocket packets was somewhat smaller for the forward chordwise location (swept pylons).

The maximum lift-drag ratios for all the configurations tested are shown in figure 7 as a function of Mach number. These data are for the unbalanced model.

Results of this investigation show that the addition of external stores could appreciably affect the trim drag of the model. This effect is illustrated in figure 8 which shows the variation of pitching-moment coefficient with lift coefficient for the basic model and for the model fitted with two external fuel tanks and four rocket packets. The magnitude of the pitching-moment coefficient at zero lift for the basic model was quite small at all Mach numbers, but the model fitted with external stores showed a significant negative pitching moment at subsonic speeds and a positive pitching moment at supersonic speeds. These pitching moments, associated with the installation of external stores on the model, significantly influence the deflection of the longitudinal control surface required for a specific flight condition. Thus it should be noted that the drag coefficients presented for this investigation are for the unbalanced model and that the total drag for the model balanced with a control device will include an additional drag increment or decrement due to the change in control setting required to counteract the aerodynamic influence of the external store. Pitching-moment characteristics are shown for the model fitted with two fuel tanks and four rocket packets because they exhibit the most pronounced effects of external stores of all the configurations investigated.

CONCLUSIONS

The following conclusions are based on a wind-tunnel investigation of the effects of external fuel tanks and externally mounted rocket packets on the drag characteristics of a model of a tailless fighter airplane:

1. The drag increase resulting from the addition of two external fuel tanks and four faired rocket packets varied from 30 percent of the drag of the basic model at 0.60 Mach number to 50 percent of the drag of the basic model at 0.90 Mach number. At Mach numbers of 1.20 to 1.70, this drag increment was approximately 30 percent of the drag of the basic model.

2. The drag coefficient, at subsonic speeds, for the model fitted with four faired rocket packets was smaller than with four open rocket packets. At supersonic speeds the four faired packets produced greater drag increments than the open packets.

3. The drag coefficients for the model fitted with two fuel tanks and four faired rocket packets were somewhat less, at supersonic speeds, with the outboard rocket packets and fuel tanks in a forward chordwise location. At subsonic speeds the chordwise location caused no significant effect on the drag characteristics.

Ames Aeronautical Laboratory
National Advisory Committee for Aeronautics
Moffett Field, Calif.

REFERENCES

1. Smith, Willard G.: Wind-Tunnel Investigation at Subsonic and Supersonic Speeds of a Model of a Tailless Fighter Airplane Employing a Low-Aspect-Ratio Swept-Back Wing - Stability and Control. NACA RM A52J30, 1952.
2. Frick, Charles W., and Olson, Robert N.: Flow Studies in the Asymmetric Adjustable Nozzle of the Ames 6- by 6-Foot Supersonic Wind Tunnel. NACA RM A9E24, 1949.
3. Olson, Robert N., and Mead, Merrill H.: Aerodynamic Study of a Wing-Fuselage Combination Employing a Wing Swept Back 63° . - Effectiveness of an Elevon as a Longitudinal Control and the Effects of Camber and Twist on the Maximum Lift-Drag Ratio at Supersonic Speeds. NACA RM A50A31a, 1950.
4. Silverstein, Abe, and White, James A.: Wind-Tunnel Interference with Particular Reference to Off-Center Positions of the Wing and to the Downwash at the Tail. NACA Rep. 547, 1935.
5. Herriot, John G.: Blockage Corrections for Three-Dimensional-Flow Closed-Throat Wind Tunnels, with Consideration of the Effect of Compressibility. NACA Rep. 995, 1950. (Formerly NACA RM A7B28)
6. Phelps, E. Ray, and Lazzeroni, Frank A.: Wind-Tunnel Investigation of the Aerodynamic Characteristics of a 1/15-Scale Model of the Northrop MX-775A Missile. NACA RM A51E28, 1951.

7. Hall, Charles F., and Heitmeyer, John C.: Aerodynamic Study of a Wing-Fuselage Combination Employing a Wing Swept Back 63° . - Characteristics at Supersonic Speeds of a Model with the Wing Twisted and Cambered for Uniform Load. NACA RM A9J24, 1950.

TABLE III.- CONTINUED
(c) Tests 24 through 38

Test No.	α	C_L	C_D	C_M	C_I	L/D	Test No.	α	C_L	C_D	C_M	C_I	L/D	Test No.	α	C_L	C_D	C_M	C_I	L/D
24	-0.13	-0.036	0.0480	0.015	-0.0002	-	29	-0.60	-0.036	0.047	-0.008	-0.0010	-	34	0.56	0.022	0.0470	0.002	-0.0007	0.47
	-2.19	-1.34	0.0476	0.03	-0.0002	-		-2.87	-1.23	0.0490	-0.005	-0.0012	-		2.17	0.088	0.0490	-0.013	-0.0010	1.80
	-0.75	0.02	0.0469	0.006	-0.0004	0.29		0.38	0.008	0.041	-0.009	-0.0010	0.77		4.88	0.176	0.0776	-0.034	-0.0014	3.05
	2.20	1.01	0.0427	-0.009	-0.0004	2.36		2.19	1.01	0.012	-0.012	-0.0009	6.65		6.39	0.257	0.0720	-0.077	-0.0015	3.68
	4.37	2.30	0.0327	-0.034	-0.0007	4.30		4.10	2.19	0.028	-0.018	-0.0006	10.02		8.70	0.354	0.0934	-0.079	-0.0019	3.79
25	6.74	3.65	0.0774	-0.085	-0.001	4.86	30	6.61	3.50	0.046	-0.028	0.006	8.62	35	-0.56	-0.029	0.0137	-0.008	-0.0013	-
	8.69	4.93	1.068	-0.095	0.006	4.62		8.83	4.87	0.048	-0.043	0.012	6.72		-2.21	-1.10	0.0162	-0.006	-0.0013	-
	-0.10	-0.022	0.0423	0.012	-0.0011	-		-0.63	-0.048	0.0187	-0.009	-0.0011	-		0.39	0.011	0.0132	-0.009	-0.0011	0.83
	-2.15	-1.12	0.0476	0.03	-0.0010	-		2.15	1.05	0.0170	-0.011	-0.0011	6.11		2.15	0.094	0.0146	-0.011	-0.0010	6.42
	0.75	0.022	0.0418	0.003	-0.0012	2.3		4.48	0.004	0.0173	-0.015	-0.0010	6.11		4.32	0.203	0.0222	-0.015	-0.0005	9.56
26	2.20	1.06	0.0442	-0.015	-0.0015	2.10	31	6.73	4.43	0.0294	-0.023	-0.0008	9.56	36	6.48	3.80	0.0325	-0.023	-0.0005	9.56
	4.37	2.24	0.0773	-0.041	-0.0015	4.04		4.09	0.029	0.0295	-0.046	-0.0004	8.10		8.65	4.39	0.0349	-0.033	-0.001	8.00
	6.49	3.40	0.0773	-0.069	-0.0009	4.20		8.82	5.11	0.071	-0.075	-	5.90		-2.88	-1.24	0.0148	-0.008	-0.0009	-
	8.64	4.91	1.078	-0.094	-0.001	4.35		-0.44	-0.048	0.0466	0.019	0	-		2.88	-1.24	0.0148	-0.008	-0.0009	-
	-0.10	-0.017	0.0423	0.011	-0.0016	-		-2.19	-1.45	0.0733	0.039	0	-		1.05	0.038	0.0142	-0.012	-0.0010	2.67
27	-2.15	-1.01	0.0472	0.030	-0.0015	-	32	2.19	0.090	0.0475	-0.006	-0.0004	1.98	37	2.19	1.02	0.0154	-0.013	-0.0008	6.61
	0.75	0.022	0.0420	0.002	-0.0019	2.22		4.35	2.21	0.0722	-0.033	-0.0006	4.01		4.40	2.21	0.0221	-0.019	-0.0005	9.99
	2.16	0.085	0.0472	-0.016	-0.0013	2.82		6.72	4.78	0.0760	-0.065	0	4.71		6.62	4.32	0.0410	-0.038	-0.0004	8.58
	4.27	2.174	0.0742	-0.037	-0.0016	3.70		8.67	4.87	1.066	-0.096	-	4.57		8.85	4.90	0.0720	-0.040	-0.0005	6.61
	6.45	3.09	0.0789	-0.067	-0.0016	4.84		-0.10	-0.017	0.0468	0.018	-0.0011	-		-0.64	-0.046	0.0188	-0.012	-0.0010	-
28	8.58	4.10	0.0984	-0.092	-0.0013	4.17	33	-0.10	-0.027	0.0468	0.018	-0.0011	-	38	-2.17	-1.19	0.0260	-0.006	-0.0013	-
	-0.10	-0.014	0.0495	0.008	-0.0007	-		-2.04	-1.15	0.0722	0.036	-0.0012	-		-2.35	-1.19	0.0260	-0.006	-0.0013	-
	-2.13	-1.07	0.0471	0.004	-0.0003	-		2.20	1.00	0.0476	-0.010	-0.0016	2.10		0.48	0.006	0.0171	-0.013	-0.0010	3.5
	0.74	0.028	0.0430	0	-0.0019	1.2		4.35	2.17	0.0772	-0.038	-0.0014	3.76		2.21	1.02	0.0175	-0.015	-0.0011	2.33
	2.16	0.085	0.0472	-0.016	-0.0013	2.82		6.49	4.78	0.0772	-0.067	-0.0009	4.94		4.46	4.09	0.0204	-0.044	-0.0008	6.16

TABLE III.- CONCLUDED
(d) Tests 39 through 43

Test No.	α	C_L	C_D	C_M	C_I	L/D
39	-0.40	-0.085	0.0460	0.015	-0.0012	---
	-2.16	-0.115	0.011	0.033	-0.003	---
	.57	.080	.0454	.006	-.0014	0.44
	1.11	.044	.0456	.001	-.0015	.96
	2.20	.101	.0475	-.012	-.0018	2.12
	4.35	.219	.0581	-.039	-.0015	3.77
	6.49	.337	.0774	-.067	-.0009	4.36
	8.63	.445	.1048	-.093	0	4.24
	-.39	-.018	.0457	.013	-.0017	---
	-2.14	-.102	.0498	.030	-.0014	---
40	.57	.084	.0454	.004	-.0020	.53
	1.11	.044	.0456	-.001	-.0021	.96
	2.20	.099	.0478	-.014	-.0020	2.07
	4.33	.205	.0778	-.039	-.0018	3.57
	6.46	.309	.0792	-.065	-.0015	4.11
	8.58	.408	.1001	-.089	-.0011	4.08
	-.39	-.018	.0457	.013	-.0017	---
	-2.14	-.102	.0498	.030	-.0014	---
	.57	.084	.0454	.004	-.0020	.53
	1.11	.044	.0456	-.001	-.0021	.96
41	2.20	.099	.0478	-.014	-.0020	2.07
	4.33	.205	.0778	-.039	-.0018	3.57
	6.46	.309	.0792	-.065	-.0015	4.11
	8.58	.408	.1001	-.089	-.0011	4.08
	-.39	-.011	.0462	.007	-.0008	---
	-2.13	-.089	.0496	.024	-.0003	---
	.57	.080	.0460	0	-.0009	.44
	1.09	.043	.0460	-.005	-.0010	.93
	2.17	.090	.0482	-.016	-.0012	1.87
	4.28	.179	.0770	-.036	-.0015	3.14
42	6.40	.268	.0719	-.058	-.0017	3.72
	8.51	.358	.0937	-.080	-.0018	3.82
	-.34	-.020	.0109	-.003	-.0013	---
	-1.08	-.044	.0112	-.002	-.0014	---
	-3.26	-.149	.0133	.003	-.0014	---
	-6.50	-.321	.0338	.017	-.0017	---
	.53	.021	.0108	-.005	-.0012	1.97
	1.08	.049	.0112	-.006	-.0010	4.39
	2.16	.101	.0127	-.008	-.0010	7.57
	4.33	.206	.0187	-.015	-.0006	11.12
43	6.48	.318	.0322	-.024	-.0008	9.87
	8.65	.441	.0560	-.036	-.0011	7.88
	10.82	.566	.0932	-.048	-.0015	6.07
	12.96	.665	.1373	-.072	-.0015	4.84
	15.08	.730	.1879	-.084	-.0013	3.59
	17.21	0.884	0.2433	-0.069	0.0005	3.39
	19.29	.875	.2904	-.076	.0007	2.93
	21.33	.901	.3499	-.086	-.0005	2.58
	-.56	-.024	.0110	-.002	-.0011	---
	-1.11	-.051	.0115	-.002	-.0012	---
44	-3.32	-.163	.0165	-.004	-.0012	---
	-6.64	-.339	.0420	-.022	-.0015	---
	.53	.020	.0110	-.005	-.0011	---
	1.09	.051	.0113	-.006	-.0011	1.82
	2.21	.108	.0130	-.010	-.0010	4.51
	4.40	.223	.0205	-.017	-.0008	8.28
	6.61	.351	.0338	-.023	-.0005	8.22
	8.82	.486	.0723	-.045	-.0005	6.72
	11.00	.593	.1138	-.056	-.0011	5.21
	13.15	.676	.1590	-.062	-.0023	4.25
45	15.26	.737	.2038	-.069	-.0005	3.62
	17.36	.797	.2566	-.078	-.0008	3.10
	-.57	-.029	.0109	-.002	-.0013	---
	-1.14	-.058	.0114	0	-.0013	---
	-3.39	-.189	.0185	.010	-.0015	---
	.53	.019	.0108	-.004	-.0011	1.76
	1.11	.053	.011	-.006	-.0011	4.77
	2.29	.117	.0232	-.011	-.0010	8.88
	4.48	.249	.0230	-.023	-.0008	10.83
	6.73	.412	.0508	-.050	-.0006	8.12
46	8.92	.510	.0888	-.075	-.0005	6.16
	-.54	-.024	.0321	.004	-.0001	---
	-3.28	-.182	.0443	.078	.0004	---
	-6.52	-.383	.0743	.078	.0007	---
	.54	.021	.0248	-.004	-.0004	.60
	1.09	.053	.0252	-.009	-.0005	1.51
	2.19	.113	.0376	-.020	-.0023	3.01
	4.35	.238	.0490	-.047	-.0027	4.86
	6.61	.372	.0707	-.077	-.0030	5.29
	8.86	.499	.1017	-.106	-.0010	4.51
47	10.61	.613	.1405	-.131	-.0017	4.36
	12.96	.696	.1799	-.140	-.0025	3.87
	-.54	-.022	0.0375	0.003	-0.0009	---
	-1.09	-.051	.0363	.009	-.0009	---
	-3.23	-.162	.0442	.033	-.0006	---
	-6.47	-.340	.0718	.074	-.0002	---
	.52	.017	.0332	-.004	-.0010	0.48
	1.06	.046	.0353	-.010	-.0011	1.30
	2.17	.102	.0374	-.022	-.0012	2.73
	4.31	.214	.0480	-.047	-.0010	4.46
48	6.45	.330	.0671	-.075	-.0006	4.92
	8.59	.442	.0946	-.102	-.0006	4.67
	10.73	.541	.1248	-.127	.0009	3.28
	12.86	.644	.1716	-.149	.0013	3.75
	-.54	-.022	.0345	.004	-.0015	---
	-1.09	-.049	.0332	.009	-.0015	---
	-3.24	-.152	.0434	.032	-.0010	---
	-6.44	-.310	.0689	.070	-.0006	---
	.52	.014	.0344	-.004	-.0016	.41
	1.07	.040	.0346	-.010	-.0017	1.16
49	2.16	.092	.0368	-.021	-.0019	2.50
	4.28	.194	.0466	-.045	-.0018	4.17
	6.41	.293	.0638	-.070	-.0015	4.67
	8.54	.397	.0883	-.095	-.0012	4.50
	10.66	.491	.1198	-.118	-.0008	4.11
	12.78	.580	.1568	-.139	-.0008	3.70
	-.54	-.019	.0346	.001	-.0008	---
	-1.08	-.042	.0353	.006	-.0006	---
	-3.22	-.134	.0425	.063	-.0002	---
	-6.39	-.271	.0636	.079	.0008	---
50	.40	.012	.0342	-.006	-.0010	.55
	.94	.037	.0345	-.011	-.0012	1.01
	2.13	.082	.0366	-.022	-.0012	2.24
	4.24	.172	.0454	-.043	-.0015	3.79
	6.36	.261	.0602	-.064	-.0017	4.33
	8.47	.348	.0819	-.085	-.0016	4.25
	10.58	.430	.1089	-.105	-.0016	3.95
	12.69	.508	.1414	-.124	-.0017	3.59
	15.08	.580	.1814	-.144	-.0017	3.59
	17.21	.644	.2216	-.169	-.0013	3.75

TABLE IV.- EXPERIMENTAL PRESSURE COEFFICIENTS, C_p
(a) Basic model, $M = 1.2$

Orifice No.	Angle of attack										Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°		-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
0	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	34	-0.103	-0.076	-0.061	-0.062	-0.005	0.041	0.109	0.165	0.222	0.285
1	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	35	-0.115	-0.074	-0.062	-0.030	-0.003	0.038	0.101	0.164	0.223	0.290
2	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	36	-0.126	-0.104	-0.085	-0.053	-0.032	0.018	0.074	0.138	0.197	0.257
3	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	37	-0.141	-0.117	-0.102	-0.069	-0.052	-0.003	0.046	0.097	0.157	0.218
4	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	38	-0.156	-0.128	-0.103	-0.072	-0.057	0.004	0.061	0.112	0.172	0.233
5	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	39	-0.171	-0.141	-0.113	-0.084	-0.069	0.011	0.078	0.129	0.189	0.250
6	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	40	-0.186	-0.154	-0.125	-0.096	-0.081	0.022	0.095	0.146	0.206	0.267
7	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	41	-0.201	-0.167	-0.137	-0.108	-0.093	0.033	0.106	0.157	0.217	0.278
8	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	42	-0.216	-0.180	-0.149	-0.120	-0.105	0.045	0.118	0.169	0.229	0.290
9	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	43	-0.231	-0.193	-0.162	-0.133	-0.118	0.057	0.130	0.181	0.241	0.302
10	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	44	-0.246	-0.207	-0.176	-0.147	-0.132	0.069	0.142	0.193	0.253	0.314
11	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	45	-0.261	-0.221	-0.190	-0.161	-0.146	0.081	0.154	0.205	0.265	0.326
12	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	46	-0.276	-0.235	-0.204	-0.175	-0.160	0.093	0.166	0.217	0.277	0.338
13	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	47	-0.291	-0.249	-0.218	-0.189	-0.174	0.105	0.178	0.229	0.289	0.350
14	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	48	-0.306	-0.263	-0.232	-0.203	-0.188	0.117	0.190	0.241	0.301	0.362
15	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	49	-0.321	-0.277	-0.246	-0.217	-0.202	0.129	0.202	0.253	0.313	0.374
16	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	50	-0.336	-0.291	-0.260	-0.231	-0.216	0.141	0.214	0.265	0.325	0.386
17	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	51	-0.351	-0.305	-0.274	-0.245	-0.230	0.153	0.226	0.277	0.337	0.398
18	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	52	-0.366	-0.319	-0.288	-0.259	-0.244	0.165	0.238	0.289	0.349	0.409
19	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	53	-0.381	-0.333	-0.302	-0.273	-0.258	0.177	0.250	0.301	0.361	0.422
20	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	54	-0.396	-0.347	-0.316	-0.287	-0.272	0.189	0.262	0.313	0.373	0.434
21	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	55	-0.411	-0.361	-0.330	-0.301	-0.286	0.201	0.274	0.325	0.385	0.446
22	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	56	-0.426	-0.375	-0.344	-0.315	-0.300	0.213	0.286	0.337	0.397	0.458
23	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	57	-0.441	-0.389	-0.358	-0.329	-0.314	0.225	0.298	0.349	0.409	0.470
24	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	58	-0.456	-0.403	-0.372	-0.343	-0.328	0.237	0.310	0.361	0.421	0.482
25	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	59	-0.471	-0.417	-0.386	-0.357	-0.342	0.249	0.322	0.373	0.433	0.494
26	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	60	-0.486	-0.431	-0.400	-0.371	-0.356	0.261	0.334	0.385	0.445	0.506
27	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	61	-0.501	-0.445	-0.414	-0.385	-0.370	0.273	0.346	0.397	0.457	0.518
28	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	62	-0.516	-0.459	-0.428	-0.399	-0.384	0.285	0.358	0.409	0.469	0.530
29	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	63	-0.531	-0.473	-0.442	-0.413	-0.398	0.297	0.370	0.421	0.481	0.542
30	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	64	-0.546	-0.487	-0.456	-0.427	-0.412	0.309	0.382	0.433	0.493	0.554
31	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	65	-0.561	-0.501	-0.470	-0.441	-0.426	0.321	0.394	0.445	0.505	0.566
32	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	66	-0.576	-0.515	-0.484	-0.455	-0.440	0.333	0.406	0.457	0.517	0.578
33	1.354	1.577	1.396	1.368	1.399	1.384	1.362	1.362	1.376	1.372	67	-0.591	-0.529	-0.498	-0.469	-0.454	0.345	0.418	0.469	0.529	0.590

Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
67	-0.063	-0.131	-0.156	-0.164	-0.184	-0.222	-0.262	-0.320	-0.401	-0.451
68	-0.009	-0.096	-0.109	-0.128	-0.138	-0.147	-0.173	-0.228	-0.314	-0.332
69	-	-	-	-	-	-	-	-	-	-
70	-	-	-	-	-	-	-	-	-	-
71	-	-	-	-	-	-	-	-	-	-
72	-0.343	-0.239	-0.208	-0.198	-0.089	0.015	0.102	0.185	0.266	0.347
73	-0.304	-0.200	-0.145	-0.094	-0.072	0.022	0.098	0.174	0.245	0.306
74	-	-	-	-	-	-	-	-	-	-
75	-0.223	-0.198	-0.172	-0.158	-0.118	-0.064	-0.011	0.061	0.107	0.165
76	-0.218	-0.191	-0.174	-0.167	-0.153	-0.100	-0.044	0.013	0.081	0.104
77	-0.216	-0.208	-0.193	-0.176	-0.170	-0.087	-0.064	0.020	0.015	0.079
78	-0.169	-0.152	-0.137	-0.116	-0.097	-0.037	0.014	0.031	0.054	0.103
79	-0.211	-0.186	-0.178	-0.154	-0.135	-0.090	-0.027	0.026	0.086	0.079
80	-0.166	-0.175	-0.152	-0.158	-0.140	-0.116	-0.088	-0.021	0.018	0.033
81	-0.224	-0.132	-0.088	-0.130	-0.243	-0.448	-0.583	-0.709	-0.788	-0.736
82	-0.043	-0.072	-0.125	-0.249	-0.316	-0.466	-0.582	-0.662	-0.710	-0.789
83	-0.008	-0.085	-0.142	-0.194	-0.276	-0.398	-0.508	-0.582	-0.628	-0.709
84	-0.011	-0.096	-0.103	-0.157	-0.214	-0.329	-0.459	-0.589	-0.682	-0.749
85	-0.018	-0.071	-0.103	-0.132	-0.196	-0.303	-0.437	-0.577	-0.682	-0.752
86	-0.087	-0.149	-0.182	-0.191	-0.211	-0.244	-0.278	-0.366	-0.458	-0.526
87	-0.187	-0.226	-0.266	-0.289	-0.301	-0.336	-0.374	-0.401	-0.508	-0.542
88	-0.175	-0.204	-0.219	-0.236	-0.271	-0.304	-0.312	-0.321	-0.439	-0.486
89	-0.086	-0.169	-0.199	-0.222	-0.240	-0.256	-0.277	-0.296	-0.408	-0.472
90	-0.088	-0.214	-0.113	-0.008	-0.032	-0.170	-0.326	-0.390	-0.446	-0.481
91	-0.461	-0.321	-0.228	-0.160	-0.089	0.004	0.124	0.214	0.286	0.355
92	-0.394	-0.294	-0.218	-0.144	-0.091	0.005	0.092	0.169	0.230	0.293
93	-0.333	-0.234	-0.166	-0.105	-0.079	-0.007	0.086	0.172	0.222	0.279
94	-0.188	-0.177	-0.158	-0.118	-0.103	-0.060	-0.003	0.044	0.088	0.135
95	-0.242	-0.244	-0.231	-0.219	-0.196	-0.168	-0.106	-0.060	-0.020	0.023
96	-0.280	-0.245	-0.235	-0.216	-0.217	-0.165	-0.105	-0.045	-0.017	0.011
97	-0.223	-0.217	-0.216	-0.206	-0.203	-0.147	-0.106	-0.073	-0.037	0.031
98	-0.182	-0.205	-0.209	-0.205	-0.195	-0.146	-0.114	-0.079	-0.040	0.003

NACA

TABLE IV.- CONTINUED
(b) Basic model, $M = 1.3$

Orifice No.	Angle of attack										Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°		-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
0	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	34	-0.104	-0.091	-0.068	-0.046	-0.021	0.000	0.078	0.156	0.230	0.298
1	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	34A	-0.064	-0.059	-0.038	-0.011	-0.014	0.076	0.168	0.264	0.317	0.377
2	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	35	-0.119	-0.077	-0.087	-0.066	-0.038	0	0.049	0.096	0.153	0.203
3	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	36	-0.144	-0.131	-0.110	-0.088	-0.060	-0.030	0.017	0.066	0.113	0.169
4	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	37	-0.208	-0.215	-0.206	-0.188	-0.160	-0.126	-0.088	-0.043	0.001	0.039
5	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	38	-0.177	-0.135	-0.131	-0.100	-0.069	-0.039	-0.007	-0.027	-0.025	-0.190
6	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	39	-0.141	-0.078	-0.021	-0.074	-0.188	-0.230	-0.287	-0.303	-0.309	-0.333
7	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	40	-0.035	-0.087	-0.184	-0.154	-0.109	-0.064	-0.024	-0.017	-0.013	-0.016
8	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	41	-0.031	-0.008	-0.029	-0.107	-0.159	-0.200	-0.230	-0.251	-0.278	-0.306
9	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	42	-0.089	-0.006	-0.026	-0.084	-0.147	-0.204	-0.254	-0.294	-0.313	-0.336
10	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	43	-0.007	-0.083	-0.094	-0.080	-0.101	-0.140	-0.184	-0.220	-0.250	-0.278
11	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	44	-0.060	-0.089	-0.114	-0.141	-0.160	-0.196	-0.227	-0.254	-0.277	-0.307
12	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	45	-0.080	-0.100	-0.123	-0.141	-0.160	-0.198	-0.229	-0.250	-0.276	-0.307
13	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	46	-0.048	-0.073	-0.103	-0.139	-0.182	-0.221	-0.254	-0.284	-0.314	-0.346
14	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	47	-	-	-	-	-	-	-	-	-	-
15	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	48	-0.094	-0.080	-0.108	-0.186	-0.138	-0.169	-0.208	-0.231	-0.253	-0.293
16	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	49	-0.248	-0.163	-0.080	-0.003	-0.076	-0.164	-0.237	-0.335	-0.414	-0.475
17	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	50	-	-	-	-	-	-	-	-	-	-
18	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	51	-	-	-	-	-	-	-	-	-	-
19	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	52	-0.200	-0.171	-0.139	-0.099	-0.097	-0.001	-0.066	-0.139	-0.216	-0.293
20	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	53	-0.168	-0.130	-0.185	-0.093	-0.061	-0.006	-0.022	-0.114	-0.178	-0.235
21	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	54	-0.197	-0.188	-0.160	-0.134	-0.104	-0.066	-0.017	-0.032	-0.087	-0.143
22	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	55	-0.193	-0.180	-0.163	-0.139	-0.114	-0.064	-0.037	-0.007	-0.028	-0.092
23	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	56	-	-	-	-	-	-	-	-	-	-
24	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	57	-0.154	-0.161	-0.132	-0.140	-0.186	-0.101	-0.068	-0.089	-0.017	-0.097
25	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	58	-0.193	-0.193	-0.181	-0.163	-0.138	-0.111	-0.067	-0.033	-0.014	-0.094
26	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	59	-0.198	-0.097	-0.010	-0.071	-0.139	-0.241	-0.343	-0.443	-0.495	-0.533
27	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	60	-0.048	-0.015	-0.104	-0.183	-0.243	-0.333	-0.410	-0.477	-0.531	-0.579
28	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	61	-0.083	-0.030	-0.086	-0.139	-0.195	-0.268	-0.371	-0.436	-0.494	-0.547
29	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	62	-0.019	-0.068	-0.072	-0.123	-0.178	-0.250	-0.378	-0.443	-0.504	-0.552
30	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	63	-0.001	-0.036	-0.076	-0.108	-0.119	-0.165	-0.286	-0.380	-0.441	-0.488
31	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	64	-0.030	-0.087	-0.097	-0.119	-0.136	-0.174	-0.216	-0.307	-0.382	-0.440
32	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	65	-0.094	-0.116	-0.148	-0.170	-0.179	-0.215	-0.246	-0.310	-0.380	-0.443
33	1.438	1.437	1.448	1.449	1.463	1.479	1.494	1.443	1.432	1.411	66	-0.107	-0.135	-0.158	-0.178	-0.193	-0.218	-0.251	-0.296	-0.348	-0.404

Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
67	-0.098	-0.129	-0.151	-0.163	-0.178	-0.207	-0.236	-0.286	-0.346	-0.415
68	-0.078	-0.098	-0.111	-0.131	-0.146	-0.178	-0.199	-0.234	-0.277	-0.336
69	-	-	-	-	-	-	-	-	-	-
70	-	-	-	-	-	-	-	-	-	-
71	-	-	-	-	-	-	-	-	-	-
72	-0.289	-0.290	-0.198	-0.130	-0.101	-0.083	0.068	0.196	0.233	0.310
73	-0.293	-0.217	-0.160	-0.109	-0.068	0.001	0.073	0.196	0.219	0.266
74	-	-	-	-	-	-	-	-	-	-
75	-0.201	-0.193	-0.170	-0.138	-0.112	-0.067	-0.011	0.023	0.103	0.164
76	-0.210	-0.193	-0.174	-0.156	-0.137	-0.100	-0.047	0.019	0.066	0.120
77	-0.216	-0.203	-0.188	-0.172	-0.156	-0.129	-0.076	-0.015	0.025	0.068
78	-0.175	-0.194	-0.157	-0.127	-0.108	-0.083	-0.012	0.035	0.063	0.100
79	-0.207	-0.190	-0.176	-0.164	-0.140	-0.102	-0.022	-0.009	0.027	0.070
80	-0.210	-0.196	-0.182	-0.167	-0.148	-0.113	-0.077	-0.039	-0.005	0.028
81	-0.220	-0.196	-0.190	-0.169	-0.143	-0.108	-0.077	-0.047	-0.026	0.076
82	-0.241	-0.231	-0.200	-0.189	-0.173	-0.141	-0.104	-0.061	-0.041	0.028
83	-0.208	-0.204	-0.117	-0.108	-0.069	-0.040	-0.039	-0.044	-0.020	0.020
84	-0.002	-0.033	-0.083	-0.113	-0.190	-0.301	-0.351	-0.406	-0.463	-0.513
85	-0.011	-0.037	-0.076	-0.114	-0.145	-0.235	-0.311	-0.406	-0.478	-0.513
86	-0.088	-0.109	-0.136	-0.175	-0.177	-0.209	-0.260	-0.320	-0.389	-0.470
87	-0.178	-0.197	-0.221	-0.248	-0.277	-0.283	-0.312	-0.343	-0.396	-0.446
88	-0.177	-0.193	-0.207	-0.213	-0.225	-0.244	-0.273	-0.290	-0.328	-0.368
89	-0.198	-0.170	-0.079	-0.009	-0.284	-0.241	-0.243	-0.134	-0.061	-0.029
90	-0.111	-0.129	-0.086	-0.013	-0.087	-0.186	-0.291	-0.397	-0.497	-0.579
91	-0.169	-0.206	-0.110	-0.048	-0.091	-0.009	-0.090	-0.179	-0.269	-0.330
92	-0.228	-0.251	-0.258	-0.198	-0.187	-0.033	-0.099	-0.144	-0.212	-0.283
93	-0.297	-0.298	-0.208	-0.139	-0.091	-0.083	0.060	0.143	0.204	0.275
94	-0.234	-0.217	-0.186	-0.147	-0.112	-0.076	-0.084	0.035	0.083	0.139
95	-0.252	-0.241	-0.228	-0.203	-0.184	-0.198	-0.114	-0.078	-0.019	0.030
96	-0.264	-0.245	-0.225	-0.207	-0.188	-0.162	-0.114	-0.025	0.003	0.037
97	-0.288	-0.213	-0.204	-0.195	-0.183	-0.156	-0.110	-0.065	-0.027	0.020
98	-0.289	-0.218	-0.203	-0.198	-0.186	-0.162	-0.118	-0.075	-0.035	0.008

NACA

TABLE III.- CONTINUED
(c) Tests 24 through 38

Test No.	α	C_L	C_D	C_M	C_i	l/d	Test No.	α	C_L	C_D	C_M	C_i	l/d	Test No.	α	C_L	C_D	C_M	C_i	l/d
24	-0.13	-0.036	0.0480	0.015	-0.0002	-	29	-0.60	-0.036	0.047	-0.008	-0.0010	-	34	0.56	0.022	0.0470	0.002	-0.0007	0.47
	-2.19	-1.34	0.0476	0.03	-0.002	-		-2.87	-1.23	0.0490	-0.005	-0.0012	-		2.17	0.088	0.0490	-0.013	-0.0010	1.80
	-0.75	0.02	0.0469	0.006	-0.004	0.29		0.38	0.008	0.041	-0.009	-0.0010	0.77		4.83	0.176	0.0776	-0.034	-0.0014	3.05
	2.20	1.01	0.0477	-0.009	-0.004	2.36		2.19	1.01	0.042	-0.012	-0.0009	6.65		6.39	0.257	0.0720	-0.077	-0.0015	3.68
	4.37	2.30	0.0439	-0.034	-0.009	4.30		4.10	2.19	0.048	-0.018	-0.0006	10.02		8.70	0.34	0.0934	-0.079	-0.0019	3.79
	6.74	3.65	0.0774	-0.085	-0.001	4.86		6.61	3.50	0.046	-0.028	-0.0006	8.62		6.70	0.39	0.0934	-0.079	-0.0019	3.79
25	8.69	4.93	1.068	-0.095	0.006	4.82	30	8.83	4.87	0.048	-0.043	0.012	6.72	35	0.56	0.022	0.0470	0.002	-0.0007	0.47
	-0.10	-0.022	0.0423	0.012	-0.0011	-		-2.65	-0.048	0.0487	-0.009	-0.0011	-		2.17	0.088	0.0490	-0.013	-0.0010	1.80
	-2.15	-1.12	0.0476	0.03	-0.0010	-		0.38	0.004	0.0470	-0.011	-0.0011	0.77		4.83	0.176	0.0776	-0.034	-0.0014	3.05
	2.20	1.06	0.0442	-0.015	-0.0012	2.40		2.20	1.06	0.0473	-0.015	-0.0010	6.11		6.39	0.257	0.0720	-0.077	-0.0015	3.68
	4.37	2.24	0.0777	-0.041	-0.0015	4.04		4.16	2.43	0.0294	-0.023	-0.0008	9.56		8.70	0.34	0.0934	-0.079	-0.0019	3.79
	6.74	3.40	0.0777	-0.089	-0.0009	4.20		6.73	4.09	0.0505	-0.046	-0.0004	8.10		6.70	0.39	0.0934	-0.079	-0.0019	3.79
26	8.64	4.91	1.078	-0.094	0.001	4.35	31	8.82	4.81	0.071	-0.075	-	5.90	36	0.60	0.036	0.048	0.002	-0.0009	0.50
	-0.10	-0.017	0.0423	0.011	-0.0016	-		-2.14	-0.048	0.0466	0.019	0	-		2.28	0.036	0.048	0.002	-0.0009	0.50
	-2.15	-1.01	0.0472	0.030	-0.0015	-		0.19	-0.045	0.0733	0.039	0	-		1.05	0.036	0.048	0.002	-0.0009	0.50
	2.20	1.02	0.0420	0.02	-0.0019	2.2		2.19	-	0.0421	0.010	0	-		4.10	0.221	0.0410	-0.019	-0.0005	3.61
	4.37	2.03	0.0446	-0.015	-0.0018	2.82		4.35	2.21	0.0725	-0.006	-0.0004	1.98		6.62	0.32	0.0725	-0.006	-0.0004	3.61
	6.74	3.09	0.0789	-0.067	-0.0016	4.84		6.72	3.78	0.0760	-0.065	0	4.71		8.65	0.32	0.0725	-0.006	-0.0004	3.61
27	8.58	4.10	0.984	-0.092	0.0013	4.17	32	8.67	4.87	1.066	-0.096	-	4.57	37	0.64	0.046	0.048	0.002	-0.0010	0.50
	-0.10	-0.014	0.0495	0.008	-0.0007	-		-2.04	-0.07	0.0468	0.018	-0.0011	-		2.25	0.046	0.048	0.002	-0.0010	0.50
	-2.13	-0.87	0.0471	0.04	-0.0003	-		0.19	-0.045	0.0733	0.039	0	-		4.10	0.221	0.0410	-0.019	-0.0005	3.61
	2.20	1.02	0.0420	0.02	-0.0019	2.2		2.19	-	0.0421	0.010	0	-		6.62	0.32	0.0725	-0.006	-0.0004	3.61
	4.37	2.03	0.0446	-0.015	-0.0018	2.82		4.35	2.21	0.0725	-0.006	-0.0004	1.98		8.65	0.32	0.0725	-0.006	-0.0004	3.61
	6.74	3.09	0.0789	-0.067	-0.0016	4.84		6.72	3.78	0.0760	-0.065	0	4.71		8.65	0.32	0.0725	-0.006	-0.0004	3.61
28	8.49	3.84	0.912	-0.082	0.0021	3.88	33	8.65	4.14	1.045	-0.093	-	4.57	38	0.64	0.046	0.048	0.002	-0.0010	0.50
	-0.10	-0.014	0.0495	0.008	-0.0007	-		-2.04	-0.07	0.0468	0.018	-0.0011	-		2.25	0.046	0.048	0.002	-0.0010	0.50
	-2.13	-0.87	0.0471	0.04	-0.0003	-		0.19	-0.045	0.0733	0.039	0	-		4.10	0.221	0.0410	-0.019	-0.0005	3.61
	2.20	1.02	0.0420	0.02	-0.0019	2.2		2.19	-	0.0421	0.010	0	-		6.62	0.32	0.0725	-0.006	-0.0004	3.61
	4.37	2.03	0.0446	-0.015	-0.0018	2.82		4.35	2.21	0.0725	-0.006	-0.0004	1.98		8.65	0.32	0.0725	-0.006	-0.0004	3.61
	6.74	3.09	0.0789	-0.067	-0.0016	4.84		6.72	3.78	0.0760	-0.065	0	4.71		8.65	0.32	0.0725	-0.006	-0.0004	3.61

TABLE III.- CONCLUDED
(d) Tests 39 through 43

Test No.	α	C_L	C_D	C_M	C_I	L/D
39						
-0.40	-0.085	0.0460	0.015	-0.0012	---	---
-2.16	-0.115	0.0511	0.033	-0.003	---	---
-0.77	0.020	0.0454	0.006	-0.014	0.44	---
1.11	0.044	0.0456	0.001	-0.015	0.96	---
2.20	0.101	0.0475	-0.012	-0.018	2.12	---
4.35	0.219	0.0581	-0.039	-0.015	3.77	---
6.49	0.337	0.0774	-0.067	-0.009	4.36	---
8.63	0.445	0.1048	-0.093	0	4.24	---
40						
-0.39	-0.018	0.0497	0.013	-0.017	---	---
-2.14	-0.102	0.0498	0.030	-0.014	---	---
-0.57	0.024	0.0454	0.004	-0.020	0.53	---
1.11	0.044	0.0456	-0.001	-0.021	0.96	---
2.20	0.099	0.0478	-0.014	-0.020	2.07	---
4.33	0.205	0.0718	-0.039	-0.018	3.57	---
6.46	0.309	0.0722	-0.065	-0.015	4.11	---
8.58	0.408	0.1001	-0.089	-0.011	4.08	---
41						
-0.39	-0.011	0.0462	0.007	-0.008	---	---
-2.13	-0.089	0.0496	0.024	-0.003	---	---
-0.55	0.020	0.0460	0	-0.009	0.44	---
1.09	0.043	0.0460	-0.005	-0.010	0.93	---
2.17	0.090	0.0482	-0.016	-0.012	1.87	---
4.28	0.179	0.0710	-0.036	-0.015	3.14	---
6.40	0.268	0.0719	-0.058	-0.017	3.72	---
8.51	0.358	0.0937	-0.080	-0.018	3.82	---
42						
-0.54	-0.020	0.0109	-0.003	-0.013	---	---
-1.08	-0.044	0.0112	-0.002	-0.014	---	---
-3.26	-0.149	0.0133	0.003	-0.014	---	---
-6.50	-0.321	0.0338	0.017	-0.017	---	---
1.08	0.021	0.0108	-0.005	-0.012	1.97	---
2.16	0.049	0.0127	-0.008	-0.010	3.39	---
4.33	0.206	0.0187	-0.015	-0.006	7.57	---
6.46	0.318	0.0322	-0.024	-0.008	9.87	---
8.63	0.441	0.0560	-0.036	-0.011	7.88	---
10.82	0.566	0.0932	-0.048	-0.015	6.07	---
12.96	0.665	0.1373	-0.072	-0.015	4.84	---
15.08	0.730	0.1879	-0.084	-0.013	3.59	---
43						
17.21	0.884	0.2433	-0.069	0.0005	3.39	---
19.29	0.875	0.2904	-0.076	0.0007	2.93	---
21.33	0.901	0.3499	-0.086	-0.005	2.58	---
44						
-0.56	-0.024	0.0110	-0.003	-0.011	---	---
-1.11	-0.051	0.0115	-0.002	-0.012	---	---
-3.32	-0.163	0.0165	-0.004	-0.015	---	---
-6.64	-0.339	0.0420	-0.022	-0.015	---	---
0.53	0.020	0.0110	-0.005	-0.011	1.82	---
1.09	0.051	0.0113	-0.006	-0.011	4.51	---
2.21	0.108	0.0130	-0.010	-0.010	8.28	---
4.40	0.223	0.0205	-0.017	-0.008	10.90	---
6.61	0.351	0.0338	-0.023	0.0005	8.22	---
8.82	0.486	0.0723	-0.045	0.0005	6.72	---
11.00	0.593	0.1138	-0.056	0.0011	5.21	---
13.15	0.676	0.1590	-0.062	0.0023	4.25	---
15.26	0.737	0.2038	-0.069	0.0005	3.62	---
17.36	0.797	0.2566	-0.078	0.0008	3.10	---
45						
-0.57	-0.029	0.0109	-0.002	-0.013	---	---
-1.14	-0.058	0.0114	0	-0.013	---	---
-3.39	-0.189	0.0185	0.010	-0.015	---	---
0.53	0.019	0.0108	-0.004	-0.011	1.76	---
1.11	0.053	0.011	-0.006	-0.011	4.77	---
2.29	0.117	0.0232	-0.011	-0.010	8.88	---
4.48	0.249	0.0230	-0.023	-0.008	10.83	---
6.73	0.412	0.0508	-0.050	-0.006	8.12	---
8.92	0.510	0.0868	-0.055	---	6.16	---
46						
-0.54	-0.022	0.0375	0.003	-0.0009	---	---
-1.09	-0.051	0.0363	0.009	-0.009	---	---
-3.23	-0.162	0.0442	0.033	-0.006	---	---
-6.47	-0.340	0.0718	0.074	-0.002	---	---
0.52	0.017	0.0322	-0.004	-0.010	0.48	---
1.06	0.046	0.0353	-0.010	-0.011	1.30	---
2.17	0.102	0.0374	-0.022	-0.012	2.73	---
4.31	0.214	0.0480	-0.047	-0.010	4.46	---
6.45	0.330	0.0671	-0.075	-0.006	4.92	---
8.59	0.442	0.0946	-0.102	---	4.67	---
10.73	0.541	0.1248	-0.127	0.009	3.28	---
12.86	0.644	0.1716	-0.149	0.013	3.75	---
47						
-0.54	-0.022	0.0345	0.004	-0.015	---	---
-1.09	-0.049	0.0332	0.009	-0.015	---	---
-3.24	-0.152	0.0434	0.032	-0.010	---	---
-6.44	-0.310	0.0689	0.070	-0.006	---	---
0.52	0.014	0.0344	-0.004	-0.016	0.41	---
1.07	0.040	0.0346	-0.010	-0.017	1.16	---
2.16	0.092	0.0368	-0.021	-0.019	2.50	---
4.28	0.194	0.0466	-0.045	-0.018	4.17	---
6.41	0.293	0.0638	-0.070	-0.015	4.67	---
8.54	0.397	0.0883	-0.095	-0.012	4.50	---
10.66	0.491	0.1198	-0.118	-0.008	4.11	---
12.78	0.580	0.1568	-0.139	-0.008	3.70	---
48						
-0.54	-0.019	0.0346	0.001	-0.008	---	---
-1.08	-0.042	0.0353	0.006	-0.006	---	---
-3.22	-0.134	0.0425	0.027	-0.002	---	---
-6.39	-0.271	0.0626	0.059	0.008	---	---
0.40	0.012	0.0342	-0.006	-0.010	0.55	---
0.94	0.037	0.0345	-0.011	-0.012	1.01	---
2.13	0.082	0.0366	-0.022	-0.012	2.24	---
4.24	0.172	0.0454	-0.043	-0.015	3.79	---
6.36	0.261	0.0602	-0.064	-0.017	4.33	---
8.47	0.348	0.0819	-0.095	-0.017	4.25	---
10.58	0.430	0.1089	-0.105	-0.016	3.95	---
12.69	0.508	0.1414	-0.124	-0.017	3.59	---

NACA

TABLE IV.- EXPERIMENTAL PRESSURE COEFFICIENTS, C_p
(a) Basic model, $M = 1.2$

Orifice No.	Angle of attack										Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°		-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
0	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	34	-0.103	-0.076	-0.061	-0.062	-0.005	0.041	0.109	0.165	0.222	0.285
1	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	35	-0.115	-0.074	-0.062	-0.030	-0.003	0.038	0.101	0.164	0.223	0.290
2	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	36	-0.126	-0.104	-0.085	-0.053	-0.032	0.018	0.074	0.138	0.197	0.257
3	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	37	-0.141	-0.117	-0.102	-0.069	-0.052	-0.003	0.046	0.097	0.157	0.218
4	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	38	-0.156	-0.128	-0.103	-0.072	-0.057	0.004	0.051	0.101	0.161	0.221
5	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	39	-0.171	-0.141	-0.113	-0.082	-0.067	0.011	0.058	0.108	0.168	0.228
6	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	40	-0.186	-0.154	-0.125	-0.094	-0.079	0.018	0.065	0.115	0.175	0.235
7	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	41	-0.201	-0.167	-0.137	-0.106	-0.091	0.025	0.072	0.122	0.182	0.242
8	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	42	-0.216	-0.181	-0.150	-0.119	-0.104	0.032	0.079	0.129	0.189	0.249
9	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	43	-0.231	-0.195	-0.164	-0.133	-0.118	0.039	0.086	0.136	0.196	0.256
10	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	44	-0.246	-0.209	-0.178	-0.147	-0.132	0.046	0.093	0.143	0.203	0.263
11	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	45	-0.261	-0.223	-0.192	-0.161	-0.146	0.053	0.100	0.150	0.210	0.270
12	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	46	-0.276	-0.237	-0.206	-0.175	-0.160	0.060	0.107	0.157	0.217	0.277
13	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	47	-0.291	-0.251	-0.220	-0.189	-0.174	0.067	0.114	0.164	0.224	0.284
14	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	48	-0.306	-0.265	-0.234	-0.203	-0.188	0.074	0.121	0.171	0.231	0.291
15	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	49	-0.321	-0.279	-0.248	-0.217	-0.202	0.081	0.128	0.178	0.238	0.298
16	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	50	-0.336	-0.293	-0.262	-0.231	-0.216	0.088	0.135	0.185	0.245	0.305
17	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	51	-0.351	-0.307	-0.276	-0.245	-0.230	0.095	0.142	0.192	0.252	0.312
18	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	52	-0.366	-0.321	-0.290	-0.259	-0.244	0.102	0.149	0.199	0.259	0.319
19	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	53	-0.381	-0.335	-0.304	-0.273	-0.258	0.109	0.156	0.206	0.266	0.326
20	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	54	-0.396	-0.349	-0.318	-0.287	-0.272	0.116	0.163	0.213	0.273	0.333
21	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	55	-0.411	-0.363	-0.332	-0.301	-0.286	0.123	0.170	0.220	0.280	0.340
22	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	56	-0.426	-0.377	-0.346	-0.315	-0.300	0.130	0.177	0.227	0.287	0.347
23	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	57	-0.441	-0.391	-0.360	-0.329	-0.314	0.137	0.184	0.234	0.294	0.354
24	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	58	-0.456	-0.405	-0.374	-0.343	-0.328	0.144	0.191	0.241	0.301	0.361
25	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	59	-0.471	-0.419	-0.388	-0.357	-0.342	0.151	0.198	0.248	0.308	0.368
26	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	60	-0.486	-0.433	-0.402	-0.371	-0.356	0.158	0.205	0.255	0.315	0.375
27	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	61	-0.501	-0.447	-0.416	-0.385	-0.370	0.165	0.212	0.262	0.322	0.382
28	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	62	-0.516	-0.461	-0.430	-0.399	-0.384	0.172	0.219	0.269	0.329	0.389
29	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	63	-0.531	-0.475	-0.444	-0.413	-0.398	0.179	0.226	0.276	0.336	0.396
30	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	64	-0.546	-0.489	-0.458	-0.427	-0.412	0.186	0.233	0.283	0.343	0.406
31	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	65	-0.561	-0.503	-0.472	-0.441	-0.426	0.193	0.240	0.290	0.350	0.416
32	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372	66	-0.576	-0.517	-0.486	-0.455	-0.440	0.200	0.247	0.297	0.357	0.426
33	1.354	1.577	1.396	1.368	1.399	1.384	1.392	1.392	1.376	1.372		-0.591	-0.531	-0.500	-0.469	-0.454	0.207	0.254	0.304	0.364	0.436

Orifice No.	Angle of attack									
	-3°	-1°	0°	1°	2°	3°	4°	5°	6°	7°
67	-0.063	-0.131	-0.156	-0.164	-0.184	-0.222	-0.262	-0.320	-0.401	-0.451
68	-0.009	-0.096	-0.109	-0.128	-0.138	-0.147	-0.173	-0.228	-0.314	-0.332
69	-	-	-	-	-	-	-	-	-	-
70	-	-	-	-	-	-	-	-	-	-
71	-	-	-	-	-	-	-	-	-	-
72	-0.343	-0.259	-0.208	-0.158	-0.089	0.015	0.102	0.185	0.266	0.347
73	-0.304	-0.200	-0.145	-0.094	-0.025	0.082	0.168	0.254	0.335	0.416
74	-	-	-	-	-	-	-	-	-	-
75	-0.223	-0.158	-0.122	-0.118	-0.084	-0.021	0.061	0.107	0.165	0.225
76	-0.218	-0.151	-0.124	-0.127	-0.100	-0.044	0.013	0.021	0.04	0.04
77	-0.218	-0.151	-0.124	-0.127	-0.100	-0.044	0.013	0.021	0.04	0.04
78	-0.169	-0.132	-0.137	-0.116	-0.097	-0.037	0.014	0.031	0.054	0.053
79	-0.211	-0.185	-0.128	-0.124	-0.100	-0.021	0.028	0.017	0.086	0.079
80	-0.166	-0.175	-0.128	-0.128	-0.140	-0.115	-0.088	-0.021	0.018	0.033
81	-0.224	-0.132	-0.088	-0.130	-0.143	-0.148	-0.139	-0.109	-0.088	-0.038
82	-0.043	-0.072	-0.125	-0.149	-0.176	-0.165	-0.122	-0.082	-0.042	-0.002
83	-0.008	-0.085	-0.142	-0.194	-0.276	-0.338	-0.378	-0.422	-0.472	-0.522
84	-0.011	-0.096	-0.103	-0.125	-0.141	-0.159	-0.179	-0.199	-0.219	-0.239
85	-0.018	-0.071	-0.103	-0.132	-0.156	-0.205	-0.223	-0.237	-0.252	-0.266
86	-0.087	-0.149	-0.182	-0.191	-0.211	-0.244	-0.278	-0.312	-0.346	-0.380
87	-0.187	-0.226	-0.266	-0.289	-0.301	-0.336	-0.374	-0.412	-0.450	-0.488
88	-0.175	-0.204	-0.219	-0.236	-0.251	-0.284	-0.312	-0.341	-0.370	-0.400
89	-0.085	-0.169	-0.199	-0.222	-0.240	-0.256	-0.277	-0.296	-0.315	-0.334
90	-0.085	-0.144	-0.113	-0.088	-0.032	0.170	0.325	0.390	0.446	0.481
91	-0.421	-0.321	-0.228	-0.160	-0.089	0.044	0.154	0.214	0.286	0.355
92	-0.394	-0.294	-0.218	-0.144	-0.091	0.005	0.092	0.169	0.230	0.293
93	-0.333	-0.234	-0.166	-0.105	-0.079	-0.007	0.086	0.172	0.222	0.279
94	-0.188	-0.177	-0.158	-0.118	-0.103	-0.060	-0.003	0.044	0.088	0.135
95	-0.242	-0.144	-0.231	-0.219	-0.196	-0.168	-0.106	-0.060	-0.020	0.023
96	-0.280	-0.245	-0.235	-0.216	-0.217	-0.165	-0.105	-0.043	-0.017	0.011
97	-0.223	-0.217	-0.216	-0.206	-0.203	-0.147	-0.106	-0.073	-0.037	0.031
98	-0.182	-0.205	-0.209	-0.205	-0.195	-0.146	-0.114	-0.079	-0.040	0.003

NACA

TABLE IV.- CONTINUED
(b) Basic model, $M = 1.3$

Orifice No.	Angle of attack												Orifice No.	Angle of attack											
	-3°	-2°	0°	1°	2°	3°	4°	5°	6°	7°	8°	-3°		-2°	0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	
0	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3A	-0.104	-0.091	-0.068	-0.046	-0.021	0.000	0.072	0.146	0.220	0.294	0.368	0.442
1	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3A	-0.084	-0.059	-0.032	-0.011	-0.014	0.006	0.102	0.164	0.227	0.291	0.354	0.417
2	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3B	-0.119	-0.077	-0.037	-0.006	-0.039	0	0.099	0.166	0.233	0.300	0.367	0.434
3	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3C	-0.144	-0.111	-0.061	-0.009	-0.050	-0.083	0.043	0.103	0.163	0.223	0.283	0.343
4	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3D	-0.169	-0.136	-0.086	-0.018	-0.106	-0.185	-0.264	-0.343	-0.422	-0.501	-0.580	-0.659
5	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3E	-0.194	-0.161	-0.111	-0.039	-0.137	-0.236	-0.315	-0.394	-0.473	-0.552	-0.631	-0.710
6	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	3F	-0.219	-0.186	-0.136	-0.054	-0.152	-0.251	-0.330	-0.409	-0.488	-0.567	-0.646	-0.725
7	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	40	-0.244	-0.211	-0.161	-0.069	-0.167	-0.266	-0.345	-0.424	-0.503	-0.582	-0.661	-0.740
8	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	41	-0.269	-0.236	-0.186	-0.084	-0.182	-0.281	-0.360	-0.439	-0.518	-0.597	-0.676	-0.755
9	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	42	-0.294	-0.261	-0.211	-0.109	-0.207	-0.306	-0.385	-0.464	-0.543	-0.622	-0.701	-0.780
10	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	43	-0.319	-0.286	-0.236	-0.124	-0.222	-0.321	-0.400	-0.479	-0.558	-0.637	-0.716	-0.795
11	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	44	-0.344	-0.311	-0.261	-0.149	-0.247	-0.346	-0.425	-0.504	-0.583	-0.662	-0.741	-0.820
12	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	45	-0.369	-0.336	-0.286	-0.174	-0.272	-0.371	-0.450	-0.529	-0.608	-0.687	-0.766	-0.845
13	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	46	-0.394	-0.361	-0.311	-0.199	-0.297	-0.396	-0.475	-0.554	-0.633	-0.712	-0.791	-0.870
14	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	47	-0.419	-0.386	-0.336	-0.224	-0.322	-0.421	-0.500	-0.579	-0.658	-0.737	-0.816	-0.895
15	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	48	-0.444	-0.411	-0.361	-0.249	-0.347	-0.446	-0.525	-0.604	-0.683	-0.762	-0.841	-0.920
16	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	49	-0.469	-0.436	-0.386	-0.274	-0.372	-0.471	-0.550	-0.629	-0.708	-0.787	-0.866	-0.945
17	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	50	-0.494	-0.461	-0.411	-0.299	-0.397	-0.496	-0.575	-0.654	-0.733	-0.812	-0.891	-0.970
18	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	51	-0.519	-0.486	-0.436	-0.324	-0.422	-0.521	-0.600	-0.679	-0.758	-0.837	-0.916	-0.995
19	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	52	-0.544	-0.511	-0.461	-0.349	-0.447	-0.546	-0.625	-0.704	-0.783	-0.862	-0.941	-1.020
20	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	53	-0.569	-0.536	-0.486	-0.374	-0.472	-0.571	-0.650	-0.729	-0.808	-0.887	-0.966	-1.045
21	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	54	-0.594	-0.561	-0.511	-0.399	-0.497	-0.596	-0.675	-0.754	-0.833	-0.912	-0.991	-1.070
22	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	55	-0.619	-0.586	-0.536	-0.424	-0.522	-0.621	-0.700	-0.779	-0.858	-0.937	-1.016	-1.095
23	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	56	-0.644	-0.611	-0.561	-0.449	-0.547	-0.646	-0.725	-0.804	-0.883	-0.962	-1.041	-1.120
24	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	57	-0.669	-0.636	-0.586	-0.474	-0.572	-0.671	-0.750	-0.829	-0.908	-0.987	-1.066	-1.145
25	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	58	-0.694	-0.661	-0.611	-0.499	-0.597	-0.696	-0.775	-0.854	-0.933	-1.012	-1.091	-1.170
26	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	59	-0.719	-0.686	-0.636	-0.524	-0.622	-0.721	-0.800	-0.879	-0.958	-1.037	-1.116	-1.195
27	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	60	-0.744	-0.711	-0.661	-0.549	-0.647	-0.746	-0.825	-0.904	-0.983	-1.062	-1.141	-1.220
28	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	61	-0.769	-0.736	-0.686	-0.574	-0.672	-0.771	-0.850	-0.929	-1.008	-1.087	-1.166	-1.245
29	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	62	-0.794	-0.761	-0.711	-0.599	-0.697	-0.796	-0.875	-0.954	-1.033	-1.112	-1.191	-1.270
30	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	63	-0.819	-0.786	-0.736	-0.624	-0.722	-0.821	-0.900	-0.979	-1.058	-1.137	-1.216	-1.295
31	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	64	-0.844	-0.811	-0.761	-0.649	-0.747	-0.846	-0.925	-1.004	-1.083	-1.162	-1.241	-1.320
32	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	65	-0.869	-0.836	-0.786	-0.674	-0.772	-0.871	-0.950	-1.029	-1.108	-1.187	-1.266	-1.345
33	1.436	1.437	1.442	1.449	1.463	1.479	1.494	1.513	1.538	1.571	1.611	1.658	66	-0.894	-0.861	-0.811	-0.699	-0.797	-0.896	-0.975	-1.054	-1.133	-1.212	-1.291	-1.370

Orifice No	Angle of attack											
	-3°	-1°	0	1°	2°	3°	4°	5°	6°	7°	8°	9°
67												
68	-0.098	-0.189	-0.171	-0.163	-0.178	-0.207	-0.236	-0.266	-0.296	-0.326	-0.356	-0.386
69	-0.078	-0.098	-0.111	-0.131	-0.148	-0.178	-0.199	-0.234	-0.277	-0.306	-0.336	-0.366
70												
71												
72	-0.209	-0.290	-0.198	-0.170	-0.161	-0.283	-0.268	-0.296	-0.326	-0.356	-0.386	-0.416
73	-0.269	-0.217	-0.160	-0.109	-0.068	-0.001	-0.072	-0.136	-0.196	-0.256	-0.316	-0.376
74												
75	-0.201	-0.193	-0.170	-0.138	-0.112	-0.067	-0.011	-0.099	-0.103	-0.168	-0.228	-0.288
76	-0.210	-0.193	-0.174	-0.156	-0.137	-0.100	-0.047	-0.019	-0.066	-0.100	-0.134	-0.168
77	-0.216	-0.203	-0.188	-0.178	-0.156	-0.129	-0.076	-0.013	-0.023	-0.068	-0.102	-0.136
78	-0.173	-0.154	-0.137	-0.127	-0.108	-0.063	-0.012	-0.035	-0.063	-0.100	-0.134	-0.168
79	-0.207	-0.190	-0.178	-0.164	-0.140	-0.108	-0.099	-0.099	-0.099	-0.099	-0.099	-0.099
80	-0.210	-0.196	-0.186	-0.167	-0.148	-0.119	-0.077	-0.039	-0.009	-0.038	-0.068	-0.102
81	-0.220	-0.196	-0.190	-0.065	-0.143	-0.112	-0.078	-0.047	-0.016	-0.046	-0.076	-0.106
82	-0.041	-0.031	-0.100	-0.189	-0.269	-0.341	-0.414	-0.481	-0.541	-0.596	-0.656	-0.716
83	-0.002	-0.094	-0.117	-0.198	-0.269	-0.360	-0.439	-0.504	-0.568	-0.628	-0.688	-0.748
84	-0.003	-0.033	-0.033	-0.110	-0.190	-0.261	-0.334	-0.406	-0.478	-0.548	-0.618	-0.688
85	-0.031	-0.037	-0.076	-0.118	-0.143	-0.219	-0.311	-0.406	-0.478	-0.548	-0.618	-0.688
86	-0.068	-0.069	-0.066	-0.106	-0.179	-0.277	-0.386	-0.478	-0.548	-0.618	-0.688	-0.748
87	-0.178	-0.197	-0.221	-0.243	-0.267	-0.287	-0.312	-0.343	-0.368	-0.393	-0.418	-0.443
88	-0.177	-0.193	-0.207	-0.213	-0.228	-0.244	-0.273	-0.290	-0.316	-0.336	-0.356	-0.376
89	-0.198	-0.170	-0.079	-0.009	-0.284	-0.411	-0.443	-0.443	-0.443	-0.443	-0.443	-0.443
90	-0.131	-0.199	-0.068	-0.013	-0.067	-0.186	-0.287	-0.367	-0.427	-0.477	-0.527	-0.577
91	-0.309	-0.296	-0.210	-0.143	-0.091	-0.009	-0.090	-0.179	-0.269	-0.359	-0.449	-0.539
92	-0.308	-0.311	-0.286	-0.198	-0.127	-0.033	-0.090	-0.144	-0.218	-0.288	-0.358	-0.428
93	-0.277	-0.298	-0.280	-0.139	-0.091	-0.083	-0.080	-0.143	-0.203	-0.263	-0.323	-0.383
94	-0.234	-0.217	-0.186	-0.147	-0.112	-0.076	-0.080	-0.143	-0.203	-0.263	-0.323	-0.383
95	-0.223	-0.241	-0.222	-0.203	-0.186	-0.168	-0.143	-0.143	-0.143	-0.143	-0.143	-0.143
96	-0.244	-0.245	-0.222	-0.207	-0.188	-0.168	-0.143	-0.143	-0.143	-0.143	-0.143	-0.143
97	-0.226	-0.213	-0.204	-0.195	-0.183	-0.166	-0.140	-0.140	-0.140	-0.140	-0.140	-0.140
98	-0.209	-0.212	-0.203	-0.192	-0.186	-0.168	-0.148	-0.118	-0.072	-0.030	-0.008	0.000

TABLE IV.- CONTINUED
(c) Basic model, $M = 1.7$

Office No	Angle of attack										Office No	Angle of attack									
	-3°	-1°	0°	1°	2°	4°	6°	8°	10°	12°		-3°	-1°	0°	1°	2°	4°	6°	8°	10°	12°
0	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	35	-0.063	-0.056	-0.034	-0.012	0.006	0.046	0.097	0.136	0.176	0.224
1	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	36	-0.061	-0.070	-0.051	-0.024	-0.015	0.034	0.073	0.112	0.152	0.204
2	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	37	-0.134	-0.127	-0.115	-0.095	-0.072	-0.044	-0.006	0.029	0.071	0.114
3	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	38	-0.198	-0.197	-0.191	-0.177	-0.153	-0.120	-0.095	-0.067	-0.035	-0.003
4	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	39	-0.178	-0.110	-0.090	-0.050	-0.016	-0.031	-0.091	-0.147	-0.202	-0.252
5	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	40	-0.040	-0.011	-0.032	-0.068	-0.100	-0.135	-0.181	-0.218	-0.255	-0.297
6	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	41	-0.011	-0.054	-0.093	-0.120	-0.146	-0.179	-0.224	-0.261	-0.290	-0.317
7	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	42	-0.023	-0.036	-0.067	-0.110	-0.142	-0.181	-0.227	-0.266	-0.304	-0.337
8	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	43	-0.042	-0.009	-0.001	-0.051	-0.143	-0.146	-0.198	-0.248	-0.282	-0.316
9	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	44	-0.065	-0.054	-0.067	-0.080	-0.090	-0.114	-0.137	-0.164	-0.234	-0.302
10	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	45	-0.028	-0.062	-0.068	-0.090	-0.108	-0.122	-0.147	-0.170	-0.186	-0.261
11	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	46	-0.026	-0.051	-0.064	-0.079	-0.088	-0.113	-0.134	-0.152	-0.173	-0.219
12	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	47	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
13	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	48	-0.060	-0.034	-0.004	-0.059	-0.098	-0.195	-0.295	-0.366	-0.441	-0.513
14	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	49	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
15	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	50	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
16	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	51	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
17	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	52	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
18	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	53	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
19	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	54	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
20	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	55	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
21	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	56	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
22	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	57	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
23	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	58	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
24	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	59	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
25	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	60	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
26	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	61	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
27	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	62	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
28	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	63	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
29	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	64	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
30	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	65	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
31	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	66	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
32	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	67	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
33	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	68	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
34	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	69	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192
34A	1.561	1.587	1.598	1.571	1.595	1.601	1.588	1.577	1.557	1.543	70	-0.018	-0.048	-0.062	-0.078	-0.096	-0.114	-0.138	-0.156	-0.171	-0.192

NACA

Office No	Angle of attack									
	-3°	-1°	0°	1°	2°	4°	6°	8°	10°	12°
71	-0.187	-0.158	-0.131	-0.071	-0.041	0.023	0.100	0.168	0.241	0.349
72	-0.174	-0.141	-0.108	-0.051	0.020	0.045	0.111	0.171	0.236	0.304
73	-0.157	-0.126	-0.106	-0.073	-0.055	-0.016	0.048	0.091	0.144	0.199
74	-0.128	-0.124	-0.115	-0.085	-0.072	-0.036	0.019	0.069	0.113	0.166
75	-0.141	-0.132	-0.132	-0.109	-0.097	-0.062	-0.003	0.036	0.087	0.140
76	-0.109	-0.107	-0.102	-0.077	-0.056	-0.017	0.036	0.071	0.112	0.158
77	-0.142	-0.140	-0.137	-0.110	-0.098	-0.070	-0.021	0.018	0.060	0.089
78	-0.149	-0.145	-0.134	-0.111	-0.099	-0.071	-0.027	0.008	0.052	0.089
79	-0.178	-0.175	-0.160	-0.119	-0.066	-0.021	-0.120	-0.191	-0.271	-0.308
80	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
81	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
82	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
83	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
84	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
85	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
86	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
87	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
88	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
89	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
90	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
91	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
92	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
93	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
94	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
95	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
96	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
97	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330
98	-0.174	-0.169	-0.153	-0.047	-0.082	-0.135	-0.196	-0.241	-0.285	-0.330

TABLE IV.- CONTINUED
(d) Model with rocket packets, $M = 1.2$

Orifice No.	Angle of attack					Orifice No.	Angle of attack					Orifice No.	Angle of attack				
	-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°
0	1.360	1.375	1.384	1.371	1.384	34	----	----	----	----	----	67	----	----	----	----	----
1	----	----	----	----	----	34A	-.014	.082	.176	.299	.363	68	-.083	-.166	-.246	-.365	-.504
2	.485	.395	.287	.193	.107	35	-.103	-.048	.042	.133	.194	69	-.055	-.151	-.207	-.316	-.407
3	.401	.310	.218	.132	.057	36	-.230	-.164	-.042	.033	.168	70	----	----	----	----	----
4	.608	.569	.436	.307	.212	37	-.248	-.175	-.095	-.019	.032	71	----	----	----	----	----
5	.552	.477	.398	.320	.253	38	-.356	-.333	-.276	-.220	-.198	72	-.368	-.255	-.046	.170	.247
6	-.034	-.094	-.154	-.204	-.250	39	.159	-.123	-.497	-.704	-.745	73	-.347	-.221	-.128	.050	.334
7	-.379	-.426	-.441	.408	-.418	40	.012	-.189	-.506	-.690	-.729	74	----	----	----	----	----
8	.106	.091	.081	.051	.055	41	.033	-.122	-.430	-.644	-.702	75	-.210	-.121	-.008	.091	.149
9	----	----	----	----	----	42	.030	-.094	-.212	-.560	-.673	76	-.201	-.133	-.037	.042	.107
10	.049	-.013	-.080	-.126	-.174	43	-.016	-.112	-.222	-.382	-.646	77	-.163	-.152	-.073	.004	.068
11	----	----	----	----	----	44	-.064	-.155	-.255	-.310	-.333	78	-.173	-.115	-.034	.043	.086
12	.114	.193	.309	.424	.530	45	-.085	-.151	-.227	-.289	-.305	79	-.185	-.151	-.079	-.012	.065
13	-.060	-.036	.060	.137	.245	46	-.059	-.134	-.213	-.267	-.306	80	-.134	-.149	-.113	-.044	.101
14	-.073	-.030	.047	.134	.201	47	----	----	----	----	----	81	.162	-.146	-.577	-.726	-.727
15	.226	.234	.256	.263	.271	48	-.018	-.138	-.194	-.254	-.287	82	.003	-.252	-.576	-.704	-.720
16	.003	.059	.174	.271	.308	49	-.117	.065	.268	.384	.517	83	-.038	-.220	-.557	-.692	-.709
17	.505	.328	.153	-.031	-.162	50	----	----	----	----	----	84	-.025	-.170	-.458	-.619	-.682
18	.013	-.153	-.345	-.474	-.575	51	----	----	----	----	----	85	-.040	-.144	-.304	-.527	-.644
19	----	----	----	----	----	52	-.307	-.209	-.058	.164	.299	86	-.110	-.210	-.296	-.445	-.579
20	-.141	-.250	-.381	-.496	-.593	53	-.367	-.243	-.020	.116	.167	87	-.207	-.301	-.373	-.445	-.562
21	.034	-.060	-.135	-.227	-.397	54	-.177	-.108	0	.085	.158	88	-.167	-.244	-.297	-.337	-.511
22	.082	.007	-.080	-.167	-.247	55	-.173	-.126	-.049	.015	.071	89	-.109	-.209	-.244	-.276	.493
23	.058	-.016	-.108	-.182	-.256	56	----	----	----	----	----	90	-.297	-.060	.212	.387	.476
24	.044	-.034	-.108	-.183	-.250	57	-.157	-.103	-.029	.033	.050	91	-.363	-.166	.011	.186	.351
25	.051	-.035	-.125	-.203	-.265	58	-.185	-.157	-.083	-.005	.052	92	-.365	-.247	-.049	.203	.310
26	----	----	----	----	----	59	.129	-.168	-.610	-.753	-.753	93	-.351	-.213	.007	.206	.275
27	----	----	----	----	----	60	.002	-.246	-.577	-.715	-.752	94	-.251	-.110	.056	.135	.169
28	-.305	-.337	-.336	-.220	-.239	61	-.019	-.210	-.558	-.701	-.729	95	-.251	-.201	-.123	-.041	.017
29	-.400	-.285	-.045	.183	.408	62	-.027	-.143	-.287	-.653	-.708	96	-.252	-.188	-.131	-.051	.004
30	-.394	-.270	-.063	.133	.217	63	-.030	-.139	-.272	-.581	-.668	97	-.202	-.169	-.129	-.050	.025
31	-.155	-.087	-.012	.096	.244	64	-.061	-.157	-.271	-.518	-.642	98	-.147	-.166	-.146	-.067	.002
32	.224	.244	.290	.326	.357	65	-.105	-.203	-.313	-.475	-.635						
33	-.343	-.285	-.134	.039	.087	66	-.131	-.197	-.301	-.417	-.560						



TABLE IV.- CONTINUED
(e) Model with rocket packets, $M = 1.3$

Orifice No.	Angle of attack					Orifice No.	Angle of attack					Orifice No.	Angle of attack				
	-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°
0	1.417	1.442	1.440	1.428	1.407	34	---	---	---	---	---	67	---	---	---	---	---
1	---	---	---	---	---	34A	.047	.012	.124	.245	.395	68	-.099	-.139	-.210	-.262	-.414
2	.508	.431	.321	.228	.151	35	-.093	-.046	.041	.134	.236	69	-.060	-.115	-.175	-.226	-.315
3	.419	.346	.247	.163	.083	36	-.209	-.162	-.075	.026	.135	70	---	---	---	---	---
4	.640	.522	.377	.278	.205	37	-.258	-.220	-.128	-.030	.047	71	---	---	---	---	---
5	.585	.518	.417	.337	.266	38	-.320	-.309	-.269	-.222	-.156	72	-.310	-.226	-.092	.146	.268
6	.040	-.012	-.053	-.128	-.176	39	.128	-.023	-.255	-.434	-.551	73	-.325	-.233	-.084	.003	.209
7	-.293	-.334	-.378	-.396	-.371	40	.043	-.105	-.303	-.453	-.550	74	---	---	---	---	---
8	-.020	.057	.065	.081	.055	41	-.011	-.061	-.267	-.444	-.544	75	-.226	-.141	-.040	.082	.178
9	---	---	---	---	---	42	-.008	-.054	-.154	-.355	-.507	76	-.210	-.155	-.065	.038	.125
10	.054	.009	-.050	-.101	-.155	43	.003	-.065	-.155	-.296	-.431	77	-.209	-.171	-.084	.015	.089
11	---	---	---	---	---	44	-.068	-.127	-.204	-.273	-.381	78	-.176	-.124	-.043	.051	.123
12	.143	.226	.325	.445	.561	45	-.084	-.126	-.200	-.265	-.277	79	-.195	-.156	-.075	-.003	.054
13	-.055	-.004	.066	.158	.265	46	-.050	-.107	-.182	-.235	-.256	80	-.194	-.162	-.092	-.035	.024
14	-.055	-.011	.052	.132	.225	47	---	---	---	---	---	81	.180	-.034	-.285	-.453	-.565
15	.220	.231	.232	.252	.267	48	-.062	-.106	-.172	-.238	-.268	82	-.024	-.136	-.348	-.485	-.567
16	-.046	-.009	.085	.231	.348	49	-.226	.023	.209	.358	.446	83	-.016	-.141	-.358	-.500	-.578
17	.580	.450	.288	.125	-.027	50	---	---	---	---	---	84	.004	-.098	-.315	-.466	-.562
18	.060	-.054	-.192	-.315	-.419	51	---	---	---	---	---	85	-.012	-.086	-.246	-.425	-.524
19	---	---	---	---	---	52	-.274	-.172	-.025	.085	.292	86	-.085	-.138	-.208	-.350	-.464
20	-.139	-.218	-.312	-.409	-.487	53	-.324	-.299	-.170	.053	.183	87	-.174	-.228	-.282	-.358	-.464
21	-.027	-.089	-.196	-.291	-.397	54	-.175	-.115	-.036	.072	.170	88	-.173	-.209	-.229	-.298	-.415
22	.071	.018	-.065	-.137	-.202	55	-.177	-.136	-.064	.021	.095	89	-.140	-.191	-.223	-.238	-.390
23	.054	.005	-.082	-.150	-.209	56	---	---	---	---	---	90	-.227	-.045	.174	.357	.465
24	.041	-.005	-.082	-.150	-.207	57	-.126	-.131	-.087	-.015	.061	91	-.311	-.192	-.013	.154	.300
25	.026	-.020	-.096	-.163	-.219	58	-.173	-.159	-.095	-.017	.062	92	-.321	-.218	-.062	.067	.325
26	---	---	---	---	---	59	.169	-.050	-.316	-.483	-.590	93	-.307	-.236	-.087	.138	.304
27	---	---	---	---	---	60	.025	-.151	-.369	-.511	-.592	94	-.267	-.229	-.086	.073	.193
28	-.260	-.296	-.337	-.408	-.412	61	.006	-.114	-.316	-.468	-.561	95	-.284	-.212	-.136	-.044	.032
29	-.313	-.227	-.019	.214	.443	62	.008	-.093	-.314	-.462	-.559	96	-.266	-.208	-.135	-.042	.032
30	-.345	-.353	-.239	-.036	.190	63	-.008	-.093	-.180	-.418	-.528	97	-.235	-.190	-.131	-.045	.031
31	-.235	-.089	-.030	.062	.171	64	-.042	-.102	-.178	-.348	-.467	98	-.216	-.189	-.134	-.062	.006
32	.230	.283	.327	.361	.397	65	-.095	-.142	-.218	-.322	-.457						
33	-.348	-.303	-.207	-.052	.134	66	-.114	-.158	-.228	-.301	-.418						

NACA

TABLE IV.- CONCLUDED
(f) Model with rocket packets, $M = 1.7$

Orifice No.	Angle of attack					Orifice No.	Angle of attack					Orifice No.	Angle of attack				
	-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°		-3°	0°	4°	8°	12°
0	1.573	1.584	1.566	1.578	1.535	33	-.141	-.150	-.115	-.045	.056	65	-.033	-.081	-.168	-.238	-.292
1	-----	-----	-----	-----	-----	34	-----	-----	-----	-----	-----	66	-.048	-.084	-.175	-.221	-.276
2	.306	.433	.338	.255	.175	34A	-.026	-.018	.017	.162	.249	67	-----	-----	-----	-----	-----
3	.420	.351	.263	.190	.119	35	.046	-.029	.049	.166	.271	68	-.063	-.103	-.186	-.219	-.265
4	.489	.413	.314	.241	.172	36	-.039	-.021	.045	.114	.201	69	.019	-.069	-.121	-.163	-.203
5	.633	.556	.454	.367	.285	37	-.171	-.166	-.114	-.044	.060	70	-----	-----	-----	-----	-----
6	.195	.141	.074	.021	-.030	38	-.183	-.186	-.155	-.101	-.038	71	-----	-----	-----	-----	-----
7	-.117	-.152	-.186	-.218	-.236	39	.176	.086	-.029	-.139	-.233	72	-.146	-.146	-.059	.115	.275
8	-.062	-.105	-.087	-.030	.006	40	.036	-.032	-.119	-.193	-.262	73	-.215	-.151	-.003	.094	.238
9	-----	-----	-----	-----	-----	41	-.014	-.089	-.165	-.238	-.294	74	-----	-----	-----	-----	-----
10	.056	.038	.017	-.023	-.079	42	.028	-.073	-.167	-.245	-.310	75	-.107	-.084	-.015	.072	.193
11	-----	-----	-----	-----	-----	43	.050	-.008	-.128	-.220	-.290	76	-.117	-.117	-.057	.054	.141
12	.208	.258	.360	.467	.470	44	-.023	-.069	-.115	-.162	-.269	77	-.138	-.137	-.051	.030	.112
13	.017	.047	.111	.191	.246	45	-.026	-.077	-.125	-.163	-.246	78	-.114	-.098	-.015	.058	.144
14	.004	0	.072	.140	.227	46	-.020	-.064	-.112	-.150	-.201	79	-.136	-.120	-.066	.003	.089
15	.193	.124	.170	.173	.189	47	-----	-----	-----	-----	-----	80	-.137	-.123	-.078	-.003	.086
16	-.040	-.026	.044	.115	.204	48	-.014	-.063	-.113	-.148	-.181	81	.247	.133	.004	-.156	-.254
17	.723	.636	.488	.391	.222	49	-.029	.009	.157	.365	.490	82	.057	-.023	-.102	-.220	-.292
18	.199	.128	.046	-.046	-.128	50	-----	-----	-----	-----	-----	83	.003	-.076	-.168	-.247	-.312
19	-----	-----	-----	-----	-----	51	-----	-----	-----	-----	-----	84	-.002	-.084	-.170	-.252	-.312
20	-.090	-.146	-.182	-.229	-.269	52	-.006	.026	.090	.213	.383	85	.015	-.083	-.164	-.232	-.295
21	-.026	-.105	-.149	-.210	-.254	53	-.212	-.185	-.105	-.003	.093	86	-.028	-.082	-.181	-.256	-.302
22	.075	.035	-.016	-.071	-.151	54	-.091	-.052	-.016	.081	.175	87	-.069	-.120	-.206	-.276	-.329
23	.054	.005	-.059	-.089	-.135	55	-.098	-.092	-.030	.045	.143	88	-.088	-.123	-.207	-.277	-.330
24	.053	.010	-.059	-.089	-.131	56	-----	-----	-----	-----	-----	89	-.089	-.124	-.198	-.267	-.296
25	.036	-.008	-.059	-.107	-.144	57	-.010	-.045	-.025	.027	.103	90	.005	.079	.212	.328	.458
26	-----	-----	-----	-----	-----	58	-.114	-.105	-.049	.026	.113	91	-.100	-.083	.020	.164	.318
27	-----	-----	-----	-----	-----	59	.221	.115	.035	-.175	-.270	92	.159	-.133	.006	.128	.285
28	-.113	-.148	-.168	-.215	-.249	60	.062	-.027	-.126	-.223	-.299	93	-.166	-.119	.012	.108	.247
29	-.027	.060	.237	.376	.640	61	-.005	-.077	-.163	-.241	-.301	94	-.100	-.107	-.052	.051	.187
30	-.081	-.097	.046	.080	.274	62	.004	-.081	-.178	-.249	-.303	95	-.155	-.143	-.080	-.011	.089
31	-.146	-.113	.046	.077	.154	63	.023	-.071	-.172	-.253	-.313	96	-.165	-.146	-.086	-.048	.108
32	-.008	-.007	.096	.346	.490	64	.008	-.056	-.155	-.238	-.293	97	-.156	-.143	-.098	.011	.073
												98	-.155	-.148	-.106	-.029	.051

NACA




Figure 1.—Three-view drawing of the model showing the external fuel tanks and rocket packets.






Figure 2.-Details of the external fuel tanks with unswept and swept pylons.



Note: rocket packet shown with open tubes

Unswept pylon




*All dimensions shown in inches
unless otherwise noted*




Swept pylon

(a) *Outboard location.*

Figure 3.—Details of the rocket packets with unswept and swept pylons.



All dimensions shown in inches
unless otherwise noted



(b) Inboard location.

Figure 3. — Concluded.




Figure 4.—Dimensional sketch of the lower surface of the model with rocket packets installed, showing the pressure survey station.




Figure 5.- Variation of drag coefficient with lift coefficient for the basic model.



(a) $C_L = 0$ (b) $C_L = 0.25$

Figure 6.- Variation of Increment of drag coefficient with Mach number at 0 and 0.25 lift coefficient for the various external store configurations mounted on the model.




Figure 6.- Concluded.




Figure 7.- Variation of the maximum lift-drag ratio with Mach number for the various external store configurations mounted on the model.




Figure 8.—Variation of pitching-moment coefficient with lift coefficient for the basic model and for the model fitted with two external fuel tanks and four faired rocket packets mounted on unswept pylons.

SECURITY INFORMATION



3 1176 01434 8156

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~